



MONOGRAPH

3<sup>RD</sup> EUROPEAN YOUNG ENGINEERS CONFERENCE 2014







# EYEC Monograph 3<sup>rd</sup> European Young Engineers Conference

April 29-30<sup>th</sup> 2014 Warsaw

#### Organizer:

Scientific Club of Chemical and Process Engineering Faculty of Chemical and Process Engineering Warsaw University of Technology

#### Patronage:









### 3<sup>rd</sup> European Young Engineers Conference

www.eyec.ichip.pw.edu.pl

Copyright © 2014, Faculty of Chemical and Process Engineering, Warsaw University of Technology

> Edited by MSc Eng. Michał Wojasiński

ISBN 978-83-936575-0-6

Printed in 100 copies

The authors are responsible for the content of the papers.
All papers reviewed by Scientific Committee.

Published by:
Faculty of Chemical and Process Engineering, Warsaw University of
Technology

Printed in Poland by:
Institute for Sustainable Technologies – National Research Institute
26-600 Radom, 6/10 Pułaskiego Street,
phone (+48) 48 36-442-41,fax (+48) 48 36-447-65
http://www.itee.radom.pl

## Evaluation of drug release from electrospun nanofibers by modification of material morphology

\*Nakielski Paweł, Kowalczyk Tomasz, Kowalewski Tomasz A.
Institute of Fundamental Technological Research Polish Academy of Sciences Pawinskiego 5B, 02-109 Warsaw
e-mail: pnakiel@ippt.pan.pl

Keywords: drug delivery, electrospinning, mathematical modeling, nanofibers

The possibility of controlling drug release from nanofibrous scaffolds has attracted many researchers around the world. Recently, we showed that nanostructured material acts as an anti-liaisons barrier positively influencing glial scar formation and caused decreasing neurodegeneration [Sulejczak *Folia Neuropathol*, 2014 (in press)]. The next step is to compose nanofibers with antioxidant drug (α-tocopherol) to further limit neurodegeneration of brain tissue. Embedment of lipophilic drug in nanofibrous materials of different: porosity, material structure or fiber arrangement results in different release kinetics. In this paper we present experimental and numerical study of the influence of fiber arrangement on the drug release from nanofibrous materials. Construction of such system is a tedious experimental task. Hence, we proposed 3D finite element model prepared in COMSOL Muliphysics® which can give insight of geometrical structure impact on the drug release from the nanofibrous mat.

Two materials electrospun from 9% wt. of poly(L-lactice-co-caprolactone) containing model drug Rhodamine B (2 % wt. with respect to polymer) were prepared from solvent mixture of N,N-dimethyloformamide and chloroform (1:9 wt./wt.). Electrospinning parameters and material characterization method can be found in paper [Andrychowski, *Folia Neuropathol*, 2013, 51,147-157]. Obtained nanofibers were collected on a rotating drum (13 cm in diameter) with different rotational speed to attain random and highly oriented nanofibers.

Results obtained from experimental study showed faster release of model drug from materials with random nanofibers comparing to oriented material. Both materials has reached release saturation at 80% of initial drug loading and the time necessary to reach release plateau was 4 and 6 days for random and aligned nanofibers, respectively. Numerical studies in representative unit volume of materials with aligned and random fibers structure showed similar behavior. Release of drug from materials in random fiber structure was prolonged comparing to aligned fiber structure.

In this paper we showed that change of fiber orientation and porosity can influence drug transport. Prolonged release can be obtained for materials with high order of fiber arrangement since the short distances between fibers and lower porosity of material can alter diffusion transport in the pores. Our results suggest that inhibition of a drug release from material can be attained by a higher fiber orientation in thin membrane near material surface.

**Acknowledgement:** The first author has been supported with a scholarship from the European Social Fund, Human Capital Operational Programme. The support of NCBiR grant no 13008110 is acknowledged.